SKG-IKOB PRODUCTCERTIFICATE 555.633.06

Date of issue: 18-06-2024

Certificate holder
Karcher GmbH
Raiffeisenstrasse 32
D-74906 Bad Rappenau
T: +49 7264 91 64 -0
E: mail@karcher-design.de
I: www.karcher-design.de

CERTIFICATE

Declaration of SKG-IKOB
This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

cylinder rose

delivered under logo / brand:

Karcher

delivered under type- and / or article number:

ESR700 YY , ESR700Q YY
YY = color

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

1. PRODUCT
cylinder rose

PRODUCT TYPE
security furniture

2. TECHNICAL SPECIFICATION

Operating:	N.A.
Construction:	1 set, round or square, of an outside part and an inside part with mounting screws
System:	WITH cylinderprotection for 17 mm profile cylinder
Material:	outside part: cast stainless steel with stainless steel cover inside part: zamac with stainless steel cover
Dimension:	outside part: Ø 52x12 mm OR 52x52x12mm
	inside part: Ø 52x10 mm OR 52x52x10 mm
Fixing:	2x M5 (steel)
Intended use:	wood, PVC, metal
	in combination with mortice locks on doors

3. DELIVERY
The preconditions for correct installation and the fasteners to be used are described in the enclosed or digitally published installation instructions with the following version:
MA_ESR700(Q) - Vers. 02.01 22.11.2023

4. PERFORMANCES
A cylinder rose according this certificate fulfils the relevant requirements of BRL 3104.
A window- or door set, in which this cylinder rose is installed according the installation instructions of the certificate holder meets at least burglar resistance class 3 of NEN 5096 and RC 2N of EN 1627, if:

- the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this cylinder rose is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

- the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).